

## 650 TREADMILL

With a combination of the latest technology options and the reliability of TRUE's premium warranty, the C650 treadmill provides the performance and efficiency needed for your commercial facility. The HRC Heart Rate Control<sup>®</sup> and TRUE's low-impact Soft System<sup>®</sup> allow your users to have a first-class exercise experience. In addition, a variety of consoles are available to provide multiple levels of features, technology, and asset management.



### FEATURES

- 15.0 MPH (24 KPH) Maximum speed with 15% Maximum incline
- HRC Cruise Control<sup>®</sup> and Soft System<sup>®</sup> deck
- Reversible / Waxed Deck

### SPECIFICATIONS

#### DIMENSIONS (L X W X H)

82" x 33" x 60.3" / 208.28 cm x 83.82 cm x 153.16 cm

#### SPEED

0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)

#### INCLINE/DECLINE LEVELS

0% to 15%, (-3% to 15% with Decline)

#### PRODUCT WEIGHT

428 lbs /194.1 kg

#### COLOR

Charcoal/Black



### CONSOLE OPTIONS



**ENVISION II**  
16" Touchscreen



**ENVISION II**  
9" Touchscreen



**SHOWRUNNER II**  
16" Integrated LCD



**EMERGE II**  
LED Console



**IGNITE II**  
LED Console

# 650 SERIES



## C650 TREADMILL

TECHNICAL SPECIFICATIONS	<b>Power Source</b>	120V/20A (NEMA 5-20R receptacle) 230V/15A	
	<b>Cord Length</b>	12' / 3.7 M	
	<b>Drive Motor</b>	5 HP AC Self-Cooling Max Drive	
	<b>Power Factor Correction (PFC)</b>	Standard	
	<b>Incline Motor</b>	1,200 lbs. of Thrust	
	<b>Speed Sensor</b>	Optical	
	<b>Deck</b>	Reversible / Waxed	
	<b>Belt</b>	Maintenance Free	
	<b>Rollers</b>	3" / 8 cm w/ Shielded Bearings	
	<b>Impact System</b>	True Soft System®	
	<b>Frame Construction</b>	Robotically Welded Heavy-Gauge Steel	
	<b>Lubrication</b>	None	
	<b>Speed Range</b>	0.5 to 12 MPH / 0.8 to 19 KPH (0.5 to 15.0 MPH / 0.8 to 24 KPH with Decline)	
	<b>Incline/Decline Range</b>	0% to 15%, (-3% to 15% with Decline)	
	<b>Quick Access Control</b>	Speed and Incline on Hand Grips with Start and Stop on Quick Access Point	
	<b>Handrail Design</b>	Extended Handrails with Moisture-Resistant Grips	
	<b>Contact Heart Rate Monitoring</b>	Yes	
	<b>Wireless Heart Rate Monitoring</b>	Polar®	
	<b>AVAILABLE CONSOLES</b>	Envision II 16", Envision II 9", ShowRunner II, Emerge II, Ignite II	
	<b>ASSET TRACKING</b>	EcoFit Compatible	
	SAFETY	<b>Safety Clip</b>	Standard/Non-Removable
<b>Extended Handrails</b>		Standard	
<b>Large Straddle Covers</b>		Standard	
<b>User Detection</b>		User Present Detection™	
<b>REGULATORY APPROVALS</b>	ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC		
<b>EXTRAS</b>	<b>Accessories</b>	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit	
PHYSICAL SPECIFICATIONS	<b>Footprint</b>	82" L x 33" W x 60.3" H / 208.28 cm x 83.82 cm x 153.16 cm	
	<b>Footprint with Decline</b>	82" L x 33" W x 62.5" H / 208.28 cm x 83.82 cm x 158.75 cm	
	<b>Running Surface</b>	60" L x 22" W / 152.4 cm x 55.8 cm	
	<b>Machine Weight</b>	428 lbs / 194.1 kg	
	<b>Shipping Weight</b>	470 lbs / 213.1 kg	
	<b>Maximum User Weight</b>	500 lbs / 226.7 kg	
	<b>Step-Up Height</b>	7" / 17.7 cm (9" / 22.86 cm with Optional Decline)	
<b>Portability</b>	2 Front Transport Wheels		
WARRANTY	<b>Warranty Type</b>	Commercial (all dues paying facilities, regardless of usage)	
	<b>Frame</b>	Lifetime	
	<b>Motor</b>	5 Years	
	<b>Parts</b>	3 Years	
	<b>Labor</b>	3 Years	

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.